



## SINGLE-SPLIT FLOOR STANDING TYPE

# SRF-ZS/ZSX



SRF25,35ZS-W, 50ZSX-W

### Auto air outlet selection

In case both lower and upper air outlets can be selected.



Wireless remote control




SRC25,35ZS-W2



SRC50ZSX-W2,-W3

### Installation workability

Piping and drain hose connection can be selected out of 6-directions.



### KEY FEATURES

- The elegant semi-flat front panel in stylish white complements various room aesthetics and creates a relaxing atmosphere
- Offers options for wall hanging, floor standing, or behind-gallery installation
- Utilizes refrigerant R32 for low Global Warming Potential (GWP) and high energy efficiency
- Operates quietly with a noise level as low as 25dB(A) in cooling Ulo mode
- Includes a "flap control system" allowing users to adjust flap angles and positions according to their preference
- Equipped with an allergen-clear filter as a default feature

### SPECIFICATIONS

Indoor unit			SRF25ZS-W	SRF35ZS-W	SRF50ZSX-W
Outdoor unit			SRC25ZS-W2	SRC35ZS-W2	SRC50ZSX-W2,-W3
Power source			1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min-Max)		kW	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.1)	5.0 (1.1 - 5.6)
Nominal heating capacity (Min-Max)		kW	2.9 (0.8 - 3.7)	4.5 (0.8 - 5.2)	6.0 (0.8 - 7.4)
Power consumption	Cooling/Heating	kW	0.59 / 0.66	0.82 / 1.12	1.32 / 1.58
	EER/COP	Cooling/Heating	4.24 / 4.39	4.27 / 4.02	3.79 / 3.80
Max. running current		A	9	9	15
Sound power level	Indoor	Cooling/Heating	50 / 51	51 / 52	58 / 58
	Outdoor	Cooling/Heating	59 / 60	63 / 64	63 / 62
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	38 / 32 / 29 / 25	40 / 35 / 33 / 29	46 / 38 / 33 / 28
		Heating (Hi/Me/Lo/Ulo)	39 / 35 / 33 / 29	41 / 36 / 35 / 33	46 / 41 / 38 / 32
	Outdoor	Cooling/Heating	45 / 47	50 / 51	51 / 51
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	9.0 / 7.6 / 6.7 / 5.8	9.2 / 7.8 / 7.3 / 6.4	11.5 / 9.6 / 7.4 / 6.6
		Heating (Hi/Me/Lo/Ulo)	10.5 / 8.2 / 7.7 / 6.6	10.7 / 8.3 / 8.1 / 7.4	12.0 / 10.0 / 9.4 / 7.6
	Outdoor	Cooling/Heating	27.4 / 27.4	31.5 / 31.5	39.0 / 33.0
Exterior dimensions	Indoor	Height x Width x Depth	540 x 780(+62) x 290		640 x 800(+71) x 290
	Outdoor				
Net weight	Indoor / Outdoor	kg	18.0 / 31.0	19.0 / 34.5	19.0 / 45.0
	Type/GWP		R32 / 675		
Refrigerant	Charge	kg/CO <sub>2</sub> Eq	0.62 / 0.419	0.78 / 0.527	1.30 / 0.878
	Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")		
Refrigerant piping size					
Refrigerant line (one way) length [chargeless length]		m	Max.20 [10]	Max.20 [15]	Max.30 [15]
Vertical height differences		Outdoor is higher/lower	Max.10 / Max.10		Max.20 / Max.20
Outdoor operating temperature range	Cooling	°CDB	-15 to 46		
	Heating		-15 to 24		
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1		

- The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
- 'tonne(s) of CO<sub>2</sub> equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.